

APPARATUS FOR DIVIDING, COMPRESSING AND TRANSMITTING VIDEO
DATA

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to an apparatus for dividing, compressing and transmitting video data that improves encoding efficiency without requiring preferential transmission of basic data.

10 Description of the Related Art

In an environment where the transmission quality largely varies (particularly, in an environment where the transmission speed varies largely), a method for enabling reception of images having an image quality corresponding to its quality has been heretofore studied, and as one method, application of scalability encoding has been tried. Conventional scalability encoding (hereinafter, referred to as "first scalability encoding") is divided largely into the followings:

- 20 1) time scalability capable of selecting the resolution in the direction of time stepwise;
- 2) space scalability for changing the space resolution;
- 3) data partitioning for dividing the frequency elements; and
- 25 4) SNR scalability for selecting encoding distortion stepwise.

0963576-092701

However, these scalability encoding makes normal reception of the basic data on a reception side a precondition. Therefore, on a transmission side, it is necessary to transmit the basic data preferentially.

5 On the other hand, scalability encoding in which the above-described basic data is not necessarily transmitted preferentially (hereinafter, referred to as "second scalability encoding") has been proposed. This method is referred to as "flat multi-scalable encoding" and uses
10 transmission using a redundant system. This method, however, transmits data encoded respectively independently, via a corresponding channel, respectively, and the reception side performs processing for averaging these data. Therefore, there is a problem in that it is not sufficient
15 in view of the encoding efficiency.

As described above, the first scalability encoding method has a problem in that the basic data must be transmitted preferentially, and the second scalability encoding method has a problem in that the encoding efficiency is not
20 sufficient.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an apparatus for dividing, compressing and transmitting
25 video data that can sufficiently improve the encoding efficiency, without requiring preferential transmission of

the basic data.

In order to achieve the object, this invention is characterized in that an apparatus for dividing, compressing and transmitting video data that uses a plurality of channels for transmission, at least comprises: a first encoding section for encoding an original picture and transmitting it with a first channel; a first compensation section for generating a first compensated original picture obtained by adding and subtracting to/from said original picture a value obtained by dispersing an encoding error occurred in said first encoding section to the remaining channels; and a second encoding section for encoding said first compensated original picture and transmitting it through a second channel.

According to the invention, an apparatus for dividing, compressing and transmitting video data that can sufficiently improve the encoding efficiency without requiring preferential transmission of the basic data can be provided.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a construction of one embodiment of the present invention;

Fig. 2 is a diagram representing the operation on the transmission side in Fig. 1;

Fig. 3 is a graph comparing the encoding efficiency

by means of the conventional time scalability and the encoding efficiency obtained by the present invention; and Fig. 4 is a graph representing changes in the encoding efficiency of patterns 1, 2 and 3 obtained on the reception side.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention will now be described in detail, with reference to the drawings. Fig. 1 is a block diagram showing a construction of one embodiment of the present invention, and constructions on the transmission side and on the reception side are shown. The present invention is characterized by the construction on the transmission side.

An encoding apparatus on the transmission side comprises: first, second and third encoding sections 1, 2 and 3 in MPEG2 or the like; first, second and third decoding sections 4, 5 and 6 such as a local decoder in MPEG2 or a decoder for decoding a bit stream; and first, second and third compensation sections 7, 8 and 9.

The first encoding section 1 encodes an original picture S(1) and outputs it to a communication line 21 of a first channel. The encoded image data is decoded in the first decoding section 4. This decoded data C(1) is input to the first compensation section 7. To the first compensation section 7 are input the original picture S(1) and the decoded data C(1). The first compensation section 7 performs

calculation of an expression (1) described below to generate a first compensated original picture S(2).

$$S(i+1) = (S(1) \times i - \sum_{k=1}^i C(k)) / (N-i) + S(1) \quad \dots (1)$$

5 where, $i = 2$ to N , and N denotes the total number of channels in the image encoding.

The first compensated original picture S(2) is encoded in the second encoding section 2, and output from a communication line 22 of a second channel.

10 Then, the image data encoded in the second encoding section 2 is decoded in the second decoding section 5, and the decoded data C(2) is input to the second compensation section 8. To the second compensation section 8 are input the original picture S(1) and the decoded data C(1) and C(2).

15 The second compensation section 8 performs calculation of the above expression (1) to generate a second compensated original picture S(3). The second compensated original picture S(3) is encoded in the third encoding section 3, and output from a communication line 23 of a third channel.

20 The operation similar to that described above is performed for each of the total number of channels N .

On the other hand, the reception side has decoding sections 51, 52, 53, ... connected to each of the number of channels N , and to each decoding section 51, 52, 53, ... are
25 connected switches 54, 55, 56, ... expressed simply. These switches 54, 55, 56, ... represent the state of the channel

0963576-002701

such as a mobile application, and if the channel is interrupted due to some reason (for example, because it is in a shadow of a building), the switch is opened. The image data received by the N channel and decoded by the decoding section 51, 52, 53, ... is added by an adder 57 and averaged by an averaging section 58, and the image data is output as an output image signal R.

If the output image signal R is expressed by an expression, the following expression (2) is obtained:

$$R = \sum_{k=1}^N C(k) \times P(k) / \sum_{k=1}^N P(k) \quad \dots (2)$$

where $P(k)$ ($k=1, \dots, N$) is 0 (when data cannot be received) or 1 (when data can be received).

Fig. 2 shows the operation on the transmission side in Fig. 1 schematically. From this figure, it can be seen that the first compensated original picture $S(2)$ becomes $\{(S(1) - C(1)) / (N-1) + S(1)$, and the second compensated original picture $S(3)$ becomes $[\{(S(1) - C(1)) + \{(S(1) - C(2))\} / (N-2) + S(1)$. Looking at these first and second compensated original pictures $S(2)$, $S(3)$, it is seen that the first and second compensated original pictures $S(2)$, $S(3)$ are the ones obtained by adding to the original picture $S(1)$ a value obtained by dispersing an encoding error occurred in the first and second encoding sections 1, 2 to the remaining channels.

Therefore, if the reception side decodes the encoded

an SNR value at the time of receiving with $ch1$, $ch1+2$, $ch1+2+3$, $ch1+2+3+4$ and $ch1+2+3+4+5$, respectively. Each point on the other curves q and r is likewise.

As is obvious from the figure, since either of each
5 curve p , q , r is upward slanting to the right, it is seen that as the number of channels decoded on the reception side increases, the encoding efficiency is improved largely.

As is obvious from the above description, according to the present invention, an apparatus for dividing,
10 compressing and transmitting video data that can sufficiently improve the encoding efficiency without requiring preferential transmission of the basic data can be provided. Moreover, there can be provided an image encoding and transmitting apparatus using multi-channels
15 which give high synthetic image quality on the reception side.

Moreover, according to the present invention, video data can be divided, encoded and transmitted, only by performing quite simple operation such as arithmetic
20 operation, other than normal encoding and decoding processing.